

## SOLYX® Glass Finishes SXJ-0550 White Dusted Matte



### Product Description

**SOLYX® SXJ-0550 White Dusted Matte** is a frosted polyester with a translucent effect. Ideal for obscuring direct visibility and allows excellent light transmission.

#### Specifications

|                            |                         |
|----------------------------|-------------------------|
| Product Code               | SXJ-0550                |
| Product Family             | Simple Frosted          |
| Film Type                  | Polyester               |
| Adhesive Type              | Pressure-sensitive      |
| Usage                      | Interior or Exterior    |
| Available Width(s)         | 60" (1524mm)            |
| Length                     | 100 linear feet (30.5m) |
| Thickness                  | 2 mil                   |
| Shading Coefficient        | 0.82                    |
| Visible Light Reflection   | 28%                     |
| Visible Light Transmission | 12%                     |
| UV Transmission            | 2%                      |
| Solar Heat Reflection      | 22%                     |
| Solar Heat Transmission    |                         |
| Solar Energy Absorbed      | 18%                     |
| Infra-Red Transmission     | 80%                     |
| U Value                    | 0.99                    |

### Product Construction

#### Face Film

2 mil polyester

#### Adhesive

Clear, Pressure-sensitive

#### Release Liner

Silicone

### Product Details

**SOLYX® SXJ-0550 White Dusted Matte** film is designed for application to interior glass, single or double pane and exterior facing glass. This film can also be installed on exterior applications. Made of durable Polyester with a matte printed surface, perfect for privacy, decorative or architectural applications. The total nominal thickness is 2 mil (50 micron). Manufactured with a silicone liner, which protects the clear, pressure-sensitive adhesive, and applied using the same tools and techniques for window films.

### Fire Rating

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

### Installation and Warranty

#### Installation

Installation should be in accordance with manufacturer's installation instructions.

#### Warranty

This **SOLYX®** product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details

### Product Distribution and Contact Information

#### Distribution

**SOLYX® Decorative Films** are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC.

Samples submitted upon request.

#### Contact Information

Decorative Films, LLC  
1-888-657-5224  
[www.decorativefilm.com](http://www.decorativefilm.com)